



HP LaserJet Enterprise MFP M528dn Monochrome All-in-One Printer

Product Specification

Brand	HP
Series	LaserJet Enterprise
Model	MFP M528dn
Part Number	1PV64A
Type	Monochrome All-in-One Printer
Available Functions	Print Copy Scan
Printing Method	Laser
Print Speed Black	Normal: Up to 43 ppm (default) Up to 50 ppm (HP High Speed)
First page out (ready) black	Black: As fast as 6 sec
Duty cycle (monthly, A4)	Up to 150,000 pages
Recommended monthly page volume	2,000 to 7,500
Print quality black	Up to 1200 x 1200 dpi

Print Resolution Technologies	300 dpi 600 dpi HP FastRes 1200 HP ProRes 1200
Paper Handling Input, Standard	100 sheet multipurpose Tray 1 550 sheet input Tray 2 automatic duplex printing
Maximum output capacity (sheets)	Up to 250 sheets
Duplex printing	Automatic (standard)
Media types	Paper (bond, colour, plain, preprinted, prepunched, recycled, rough) Envelopes Labels Cardstock Transparencies User-defined
Media sizes supported	Tray 1: A4 A5 A6 RA4 B5 (JIS) B6 (JIS) 10 x 15 cm Oficio (216 x 340) 16K postcards (JIS single and double) envelopes (B5, C5, C6, DL) Tray 2: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), Oficio (216 x 340), 16K, postcards (JIS double) Optional 550 sheet Tray: A4 A5 A6 RA4 B5 (JIS) B6 (JIS) Oficio (216 x 340) 16K postcards (JIS double)
Scanner Type	Flatbed, ADF
Scan file format	PDF JPEG TIFF MTIFF XPS PDF/A
Scan resolution, optical	Up to 600 dpi
Scan speed (normal, A4)	Up to 43 ppm/43 ipm (black and white), up to 38 ppm/38 ipm (colour)
Recommended monthly scan volume	4000 to 7000
Automatic document feeder capacity	Standard, 100 sheets
Copy speed (normal)	Black: Up to 43 cpm (default) Up to 50 cpm (HP High Speed)
Copy resolution (black text)	Up to 600 x 600 dpi
Copy resolution (color text and graphics)	Up to 600 x 600 dpi
Copy reduce / enlarge settings	25 to 400%

Copies, maximum	Up to 9999 copies
Display	20.3 cm (8.0 in) touchscreen (1024 x 768) LCD (colour graphics) smooth gesture enabled touchscreen
processor Speed	1.2 GHz
Memory	1.25 GB (printer) 512 MB (Scanner)
Connectivity, standard	1 Hi-Speed Device USB 2.0 2 Hi-Speed USB 2.0 Host 1 Gigabit Ethernet 1 Hardware Integration Pocket
Operating Temperature Range	10 to 32.5°C
Recommended operating humidity range	30 to 70% RH