



HP LaserJet Enterprise M612dn Single Function Laser Printer

Product Specification

| | |
|------------------------------|-----------------------|
| Brand | HP |
| Series | LaserJet Enterprise |
| Model | M612dn |
| Part Number | 7PS86A |
| Type | Printer |
| Functions | Print |
| Printing Method | Laser |
| Print Speed | Up to 75 ppm |
| First page out (ready) black | As fast as 5.0 sec |
| Resolution | Up to 1200 x 1200 dpi |
| Monthly duty cycle | Up to 300,000 pages |
| Paper trays, standard | 2 |
| Paper Trays, Maximum | Up to 6 |

| | |
|---------------------------------|--|
| Paper Handling Input, Standard | 100-sheet multipurpose feeder 550-sheet input feeder |
| Paper handling output, standard | 500 sheet output bin |
| Duplex printing | Automatic (standard) |
| Finished output handling | Sheetfed |
| Media types | Paper (plain, light, bond, recycled, heavy, extra heavy, cardstock, pre-printed, pre-punched, colored, rough, heavy rough) mono transparency labels letterhead envelope heavy envelope |
| Display | 4.3-in (10.92 cm) Color Graphics Display (CGD) with touchscreen; rotating (adjustable angle) |
| processor Speed | 1.2 GHz |
| Connectivity, standard | 1 Hi-Speed USB 2.0 Device 2 Hi-Speed USB 2.0 Host 1 Gigabit Ethernet 10/100/1000T network 1 Hardware Integration Pocket |
| Memory | 512 MB |
| Power | 100V - 127V nominal @ +/-10% (min 90V, max 140V) 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 12 A 220V - 240V nominal, @ +/-10% (min 198V, Max 264V) 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 6 A. Not dual voltage, power supply varies by part number with Option code identifier |
| Power Consumption | 877 watts (printing) 14.98 watts (ready) 4.28 watts (sleep) < 0.1 watts (Auto Off/Manual On) < 0.1 watts (Manual Off) |
| Operating Temperature Range | 50 to 91°F |
| Operating humidity range | 30 to 70 % RH |