



D-Link DSL-2520U ADSL2/2+ Router with USB and Ethernet Ports

#### Product Specification

Brand	D-Link
Model	DSL-2520U
LED Indicators	Power   Status   LAN   USB   DSL   Internet
ADSL	1 RJ-11 port
RJ45 Port (Lan Port)	1 RJ-45 10/100BASE-TX Fast Ethernet port with auto-MDI/MDIX
USB Port	1 port 1.1, type B
QoS	Interface grouping   3 priority queues
ADSL Standards	ADSL: Full rate ANSI T1.413 Issue 2, ITU-T G.992.1 (G.dmt) Annex A, ITU-T G.992.2 (G-lite) Annex A, ITU-T G.994.1 (G.hs)   ADSL2: ITU-T G.992.3 (G.dmt.bis) Annex A/L/M, ITU-T G.992.4 (G-lite.bis) Annex A   ADSL2+:ITU-T G.992.5 Annex A/M
WAN Connection Types	PPPoE   PPPoA   IpoA   Static IP   Dynamic IP Bridge
ATM/PPP Protocols	Bridged and routed Ethernet encapsulation   VC-based or LLC-based multiplexing   ATM Forum UNI3.1/4.0 PVC (up to 8 PVCs)   ATM Adaptation Layer Type 5 (AAL5)   ITU-T I.610 OAM F4/F5 loopback   ATM QoS   PPP over ATM (RFC 2364)   PPP over Ethernet (PPPoE)   Keep-alive for PPP connections
Network Protocol	Static IP routing   NAT   DHCP server/client/relay   DNS relay   DDNS   UpnP   Support of VLAN   IGMP proxy

Security	Network Address Translation (NAT)   Stateful Packet Inspection (SPI)   URL filter   Packet filtering (IP/ICMP/TCP/UDP)   Virtual servers   Prevention of DoS attacks   Intrusion detection system   DMZ   Port Triggering
Configuration	Multilingual web-based interface for configuration and management   Access via TELNET   Firmware update via web-based interface   Saving/restoring configuration to/from file   Support of remote logging   Automatic synchronization of system time with NTP server
Power supplies	External power adapter DC 5V/1A
Additional Features	ON/OFF power switch   Reset to Factory Defaults button