



Canon Pixma iX6770 Single Function Inkjet Printer

Product Specification

Brand	Canon
Series	Pixma
Model	iX6770
Type	5-Ink Color Inkjet Printer
Available Functions	Print
Printing Resolution	4 800 (horizontal) x 1 200 (vertical) dpi
Print Head / Ink	Type:Individual Ink Tank Number of Nozzles: Total 5 120 nozzles Ink Droplet Size: 1pl Ink Tank: PGI-750 (Pigment Black), CLI-751 (Cyan / Magenta / Yellow / Black)[Optional: PGI-755 XXL (Pigment Black), PGI-750XL (Pigment Black),CLI-751XL (Cyan / Magenta / Yellow / Black)
Print Speed	Document: Col ESAT / Simplex : 10.4 images per minute Document: B/W ESAT / Simplex : 14.5 images per minute Photo (27.94 x 35.56cm image) PP-201 : 120s Photo (10.16 x 15.24 cm) PP-201 / Borderless : 36s
Printable Width	322.2mm , Borderless: 329mm
Printable Area	Borderless Printing : Top / Bottom / Right / Left margin: each 0mm (Supported Paper Size: A3+, A3, A4, I, LDR, 10.16 x 15.24cm, 12.7 x 17.78cm, 20.32 x 25.4cm, 25.4 x 30.48cm) Bordered Printing : Top margin: 3mm, Bottom margin: 5mm, Left / Right margin: each 3.4mm (I / LGL: Left: 6.4mm, Right: 6.3mm)
Recommended Printing Area	Top margin: 40.7mm / Bottom margin: 37.4mm

Paper Sizes	A3+, A3, A4, A5, B4, B5, I, LGL, LDR, 10.16 x 15.24cm , 12.7 x 17.78cm , 20.32 x 25.4cm , 25.4 x 30.48cm , Envelopes (DL, COM10), Custom size (width 55 - 329mm, length 91 - 676mm)
Paper Handling	Plain Paper : A3, A4, A5, B4, B5, I, LGL, LDR = 150 High Resolution Paper (HR-101N) : A3+ = 20, A3 = 50, A4 = 80 Photo Paper Pro Platinum (PT-101) : A3+ = 1, A3, A4 = 10, 10.16 x 15.24 cm = 20 Photo Paper Plus Glossy II (PP-201) : A3+ = 1, A3, A4 = 10, 10.16 x 15.24 cm = 20 Photo Paper Pro Luster (LU-101) : A3+ = 1, A3, A4 = 10 Photo Paper Plus Semi-Gloss (SG-201) : A3+ = 1, A3, A4, 20.32 x 25.4 cm = 10, 10.16 x 15.24 cm = 20 Glossy Photo Paper "Everyday Use" (GP-601) : A4 = 10, 10.16 x 15.24 cm = 20 Matte Photo Paper (MP-101) : A3, A4 = 10, 10.16 x 15.24 cm = 20 Envelope : European DL / US Com. #10 = 10
Ink End Sensor	Optical sensor + Dot count
Interface	USB 2.0 Hi-Speed USB
Operating Environment	Temperature: 15 - 30°C; Humidity: 10 - 80% RH (no dew condensation)
Storage Environment	Temperature: 0 - 40°C; Humidity: 5 - 95% RH (no dew condensation)
Duty Cycle	Duty Cycle
Power	AC 100 - 240V; 50 / 60Hz
Environmental	Regulation: RoHS (EU, China), WEEE (EU) Eco-Label: Energy Star, EPEAT