



Hikvision IDS-7208HUHI-M1/FA 8 Channel AcuSense DVR

Product Specification

Brand	Hikvision
Model	iDS-7208HUHI-M1/FA
Type	8 Channel AcuSense DVR
False Alarm Reduction	Up to 4-ch
Video Compression	H.265 Pro+ H.265 Pro H.265 H.264+H.264
Encoding Resolution	8 MP@8 fps 5 MP@12 fps 4 MP@15 fps 3 MP@18 fps 1080p 720p WD1 4CIF VGA CIF@25 fps (P) 30 fps (N) Sub-stream: WD1 4CIF CIF@25 fps (P) 30 fps (N)
Video Bitrate	32 Kbps to 10 Mbps
Dual Stream	Support
Stream Type	Video, Video & Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
IP Video Input	4-ch (up to 12-ch) Up to 8 MP resolution
Analog Video Input	8-channel

AHD Input	5 MP 4 MP 1080p@25 fps 1080p@30 fps 720p@25 fps 720p@30 fps
HDCVI Input	4 MP 1080p@25 fps 1080p@30 fps 720p@25 fps 720p@30 fps
VGA Output	1-ch 1920 × 1080/60Hz 1280 × 1024/60Hz 1280 × 720/60Hz 1024 × 768/60Hz HDMI/VGA simultaneous output
HDMI Output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz 1280 × 720/60Hz, 1024 × 768/60Hz HDMI/VGA simultaneous output
Audio	Input: 1-ch RCA (2.0 Vp-p, 1 KΩ) 8-ch via coaxial cable Output : 1-ch RCA (Linear, 1 KΩ)
Two-Way Audio	1-channel RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)
Network	Remote Connection : 64 Protocol TCP/IP PPPoE DHCP Hik-Connect DNS DDNS NTP SADP NFS iSCSI UPnP HTTPS ONVIF Interface 1 :RJ45 10M/100M/1000M self-adaptive Ethernet interface
Capacity	up to 10 TB capacity for each disk
Serial Interface	RS-485 (half-duplex)
USB Interface	Front panel: 1 × USB 2.0 Rear panel: 1 × USB 3.0
Power Supply	12 VDC, 2 A
Power Consumption	≤ 15 W
Operating Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Operating Humidity	10% to 90%