

## Logitech MeetUp HD Video and Audio Conferencing System

## Product Specification

Brand	Logitech
Series	MeetUp
Туре	HD Video and Audio Conferencing System
Camera	Custom Logitech lens with 5x HD zoom and motorized pan (+/- $25^{\circ}$ ) and tilt (+/- $15^{\circ}$ )
Field of View	Diagonal: 120°   Horizontal: 113°   Vertical: 80.7°
Total Room Coverage (field of view + pan and tilt)	163° wide x 110° tall   3 camera position presets
RightSight auto- framing	Requires Windows 10 64-bit or macOS 10.14 or higher
Video Performance	4K Ultra HD video calling (up to 3840 x 2160 pixels @ 30 fps with customer-supplied USB 3.0 cable)   1080p Full HD video calling (up to 1920 x 1080 pixels @ 30 fps)   720p HD video calling (up to 1280 x 720 pixels @ 30 fps)
Microphone	Integrated microphone with 3 beamforming elements   MeetUp: 4 m With optional Expansion Mic: 5 m
Sensitivity	-27 dB
Microphone frequency response	90Hz-16KHz for full voice reproduction and high intelligibility without noise

Beamforming performance	Factory-paired, very low distortion broadside beamforming algorithm steers the microphones directly at the talker for the best voice pickup and noise reduction
Microphone date rate	32KHz sampling rate
Speaker	Volume adjustable to 95 dB SPL at 1/2 meter peak   Speaker sensitivity $86.5+/-3dB$ SPL at 1/2 meter   Distortion: 200-300Hz < 3%, 3000 Hz -10KHz < 1%   Patent-pending anti-vibration enclosure improves voice clarity while limiting sound transmission to adjacent spaces
Additional Information	Bluetooth wireless technology   RF remote control   Integrated table/wall mount; optional TV mount available   Kensington security slot