



TP-Link Archer T2U Nano AC600 Wireless USB Adapter

Product Specification

Brand	TP-Link
Series	Archer T2U Nano
Model	AC600
Type	Wireless USB Adapter
Interface	USB 2.0
Antenna Type	Omni Directional
Wireless Standards	IEEE 802.11ac IEEE 802.11a IEEE 802.11n IEEE 802.11g IEEE 802.11b
Frequency	5GHz 2.4GHz
Transmit Power	<20dBm (EIRP)
Wireless Modes	Ad-Hoc Infrastructure mode
Wireless Security	Support 64/128 bit WEP WPA-PSK WPA2-PSK 802.1x
Modulation Technology	DBPSK DQPSK CCK OFDM 16-QAM 64-QAM 256-QAM
Signal Rate	5GHz-11ac: Up to 433Mbps(dynamic) 11n: Up to 150Mbps(dynamic) 11a: Up to 54Mbps(dynamic) 2.4GHz-11n: Up to 200Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)

Reception Sensitivity	5GHz-11a 6Mbps: -90dBm 11a 54Mbps: -73dBm 11n HT20 MCS0: -89dBm 11n HT20 MCS7: -70dBm 11n HT40 MCS0: -86dBm 11n HT40 MCS7: -67dBm 11ac VHT80 MCS0: -82dBm 11ac VHT80 MCS9: -56dBm 2.4GHz-11b 1Mbps: -96dBm 11b 11Mbps: -88dBm 11g 6Mbps: -89dBm 11g 54Mbps: -74dBm 11n HT20 MCS0: -89dBm 11n HT20 MCS7: -72dBm 11n HT40 MCS0: -86dBm 11n HT40 MCS7: -66dBm
System Requirements	Windows 10/8.1/8/7/XP (32/64bits) Mac OS X 10.9-10.13
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Operating Humidity	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing