



Hikvision DS-7732NI-K4 32 Channel NVR

Product Specification

Brand	Hikvision
Model	DS-7732NI-K4
Type	Embedded 4K NVR
IP Video Input	32-ch
Bandwidth	Incoming : 256 Mbps Outgoing : 160 Mbps
HDMI Output	4K (3840 × 2160)/30Hz 2K (2560 × 1440)/60Hz 1920 × 1080/60Hz 1600 × 1200/60Hz 1280 × 1024/60Hz 1280 × 720/60Hz 1024 × 768/60Hz
VGA Output	1920 × 1080/60Hz 1280 × 1024/60Hz 1280 × 720/60Hz 1024 × 768/60Hz
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1kΩ)
Decoding Format	H.265/H.265+/H.264+/H.264/MPEG4
Recording Resolution	8 MP 6 MP 5 MP 4 MP 3 MP 1080p UXGA 720p VGA 4CIF DCIF 2CIF CIF QCIF
Decoding Capability	2-ch @ 8 MP (25fps) 4-ch @ 4MP (30fps) / 8-ch @ 1080p (30fps)
Network Protocol	TCP/IP DHCP IPv4 Hik-Connect DNS DDNS NTP RTSP SADP SMTP SNMP NFS iSCSI ISUP UPnP HTTP HTTPS

Network interface	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
SATA Ports	4 SATA interfaces
Capacity	Up to 6TB capacity for each HDD
Serial Interface	1 RS-485 (half-duplex), 1 RS-232, 1 keyboard (optional)
USB Interface	Front panel: 2 × USB 2.0 Rear panel: 1 × USB 3.0