



Firewall Dinstar 32 Port VoIP Gateway|32 GSM

Product Specification

Brand	Dinstar
Model	VG-32G
Type	Gate Way
SIM Slots	32 SIM slots
Antennas	SMA
Ethernet	2*10/100 Base-T RJ45
LED Indicators	PWR RUN Signal Strength Indicators Console:1* RS232 115200bps
Network Type	Static IP, DHCP Client
Protocols	TCP/UDP,TFTP, FTP, RTP/ RTCP,ARP,RARP,ICMP, NTP, DNS
Power	100-240V,50-60Hz@External DC12V4.0A
Power Consumption	Approx. 68W
Operation Temperature	0 °C ~ 45 °C
Storage Temperature	-20 °C ~80 °C

Operating Humidity	10%-90% No Condensation
Software Features	Mobile to VoIP, VoIP to Mobile SIP Trunk and Trunk Group Port and Port Group Caller/Called Number Manipulation SIP Codes Mapping White/Black List PSTN/VoIP Hotline Abnormal Call Monitor Call Minutes Limitation Balance Check Random Call Interval Auto CLIP Signaling & RTP Encryption SMPP for SMS
Frequency Bands	Type-A: FDD: B2/B4/B12;WCDMA: B2/B4/B5 Type-E: FDD:B1/B3/B5/B7/B8/B20 TDD: B38/B40/B41 WCDMA: B1/B5/B8;GSM:900/1800MHz Type-V: FDD:B4/B13 Type-J: FDD:B1/B3/B8/B18/B19/B26 TDD:B41 WCDMA:B1/B6/B8/B19 Type-AU: FDD:B1/B2/B3/B4/B5/B7/B8/B28 TDD:B40 WCDMA: B1/B2/B5/B8;
Maintenance	HTTPS/HTTP Web Configuration Configure Backup/Restore Firmware Upgrade by HTTP/TFTP CDR(10000 Lines Storage Locally) Syslog/Filelog Ping and Tracert Traffic statistics: TCP,UDP,RTP