Logitech V-U0036 Group Video Conference System with Expansion Mics

Product Specification

| | |
|---|---|
| Brand | Logitech |
| Model | V-U0036 |
| Type | Group Video Conference System with Expansion Mics |
| Camera features | Smooth motorized pan, tilt and zoom, controlled from remote or console \| 260° pan, 130° tilt \| 10x lossless HD zoom \| 90° Field of View \| Autofocus \| 5 camera presets \| Far-end control (PTZ) of ConferenceCam products \| Kensington security slot \| LED to confirm video streaming \| Standard tripod thread |
| Speakerphone Features | Full-duplex performance \| Acoustic echo cancellation \| Noise reduction technology \| Bluetooth and NFC wireless technology \| LCD for caller ID, call duration and other functional response \| LEDs for speakerphone streaming, mute, hold, and Bluetooth wireless paring \|Touch controls for call answer/end, volume and mute, Bluetooth - plus camera PTZ, "home" preset and far-end control |
| Hub Features | Central mountable hub for connection of all components \| Included adhesive solution for under-table mounting \| Two cables for connection between hub and camera/speakerphone |
| General Features | Dual purpose mount for wall placement or for elevating the camera on a table \| UVC-compliant video and audio for broad application compatibility \| Optimized for Microsoft Lync, Certified for Skype for Business, Cisco Jabber and WebEx compatible. Enhanced integration with Logitech Collaboration Program (LCP) members \| Downloadable diagnostic tool \| Field upgradeable firmware tool \| Downloadable app plug-ins for advanced feature support |
| Lens | Field of View : 90° |
| Video Output | Broadcast System Compatibility : NTSC \| Output Formats : USB: 1920 x 1080p at 30 fps \| |
| Controls | Movement Range - Pan: 230° Tilt: 130° \| Wireless Range - 28' / 8.5 m (IR) |
| Interfaces | Video Output Connectors : 1 x USB 2.0 Type-A (USB Video) Female |

| | |
|---|---|
| Tripod Mounting Thread | 1 x 1/4"-20 Female |
| Speaker frequency response | 120 Hz to 14 kHz |
| Maximum Sound Pressure Level (SPL) | 91 dB |
| Total Harmonic Distortion (THD) | <5% |
| Microphone frequency response | 100 Hz to 11 kHz |
| Number of Mics | 4 |
| Microphone Pickup Pattern | Omnidirectional |
| Brand | |
| Model | |
| Feature | |